

Ref Code	Size	Finished	Bolt Holes	Bolt Circle	Bolt Hole Diameter	Center Bore	Inset	Outset	Weight Kg	Max Load	Valve Stem
T179A	16X5.5	Machined - Spazzolato	6	205 mm	16	161	112	126	8,2	1320 kg	TR553C
T179A	16X5.5	Polished Bothside - Lucido Int/Est	6	205 mm	16	161	112	126	8,2	1320 kg	TR553C
T160A	19.5X7.5	Polished Bothside - Lucido Int/Est	8	275 mm	30	221	134	155	18,4	3000 kg	70MS-07N
T154A	22.5X8.25	Polished Bothside - Lucido Int/Est	10	335 mm	26/32	281	144.8	167	23,2	3650 kg	70MS-07N
T154A	22.5X8.25	Full Pom-Nano - Bright	10	335 mm	26/32	281	144.8	167	23,2	3650 kg	70MS-07N
T057A	22.5X9.0	Machined - Spazzolato	10	335 mm	26/32	281	152.1	175	23,8	4125 kg	70MS-07N
T057A	22.5X9.0	Polished Bothside - Lucido Int/Est	10	335 mm	26/32	281	152.1	175	23,8	4125 kg	70MS-07N
T057A	22.5X9.0	Full Pom-Nano - Bright	10	335 mm	26/32	281	152.1	175	23,8	4125 kg	70MS-07N
T172A	22.5X11.75	Machined - Spazzolato	10	335 mm	26/32	281	120	146.3	24,5	5000 kg	60MS
T172A	22.5X11.75	Polished Outside - Lucido Esterno	10	335 mm	26/32	281	120	146.3	24,5	5000 kg	60MS
T172A	22.5X11.75	Full Pom-Nano - Bright	10	335 mm	26/32	281	120	146.3	24,5	5000 kg	60MS
T008B	22.5X11.75	Full Pom-Nano - Bright	10	335 mm	26	281	0	25	25,2	4500 kg	60MS
T246B	22.5X11.75	Polished Outside - Lucido Esterno	10	335 mm	26/32	281	135	160	24,4	5000 kg	60MS
T246B	22.5X11.75	Full Pom-Nano - Bright	10	335 mm	26/32	281	135	160	24,4	5000 kg	60MS